

MS-V Variable Speed Hoist Standard Models

Cage Type		Payload	Speed	Height	Motor Configuration	Inverter Capacity
Single	Twin	kg	m/min	m	No x Capacity	kW
MS-VL-20/32	MS-VL-20/32II	2000	0-45	300	2 x 11	45
MS-VS-20/32	MS-VS-20/32II	2000	0-60	600	3 x 11	75
MS-VH-20/32	MS-VH-20/32II	2000	0-95	600	3 x 18.5	110
MS-VL-27/32	MS-VL-27/32II	2700	0-45	300	3 x 11	75
MS-VS-27/32	MS-VS-27/32II	2700	0-60	600	3 x 15	90
MS-VH-27/32	MS-VH-27/32II	2700	0-95	600	3 x 22	132
MS-VL-32/32	MS-VL-32/32II	3200	0-45	300	3 x 15	90
MS-VS-32/32	MS-VS-32/32II	3200	0-60	600	3 x 18.5	110
MS-VH-32/32	MS-VH-32/32II	3200	0-95	600	3 x 22	132

All MS-V Models quoted at standard cage size of 3.2m x 2.5m x 1.5m. Other sizes available on request

Larger Multi-Mast Hoists available from our MS-M Series

Cage Type	Payload	Speed	Number of Masts	Cage Size
Single	kg	m/min		L x W x H (m)
MS-M-4000	4000	0-36	2	5 x 3 x 3.4
MS-M-6000	6000	0-36	2	6 x 4 x 3.4
MS-M-8000	8000	0-20	2	8 x 5 x 3.4
MS-M-10000	10,000	0-20	2	Larger Sizes Available on request
MS-M-20000	20,000	0-10	4	

Contact

UNITED ARAB EMIRATES

Mastclimber Solutions F.Z.E. , Po Box 37135, RAK, U.A.E
+971 72048587 (Office) +971 554389497 (mobile)
Info@mastclimbersolutions.com

UNITED STATES

4730 Raven Avenue, Las Vegas, NV89139, USA
USA +1 702 460 1988
Info@mastclimbersolutions.com